



# VCT-3000

## VERTICAL CASE TRANSPORT




### Vertical Case Transport

- Speeds up to 200 FPM
- Belt driven In-feed hopper
- Spring loaded hugger belt drive system
- Re-stacker
- PLC controlled, Recipes for different product setup
- Can be integrated with Printers and Labelers
- Independent Variable speed adjustment
- NO PLANT AIR needed
- Processing two sides of the case in one pass



# VCT-3000 VERTICAL CASE TRANSPORT



- PLC controlled, touch screen interface
- Stainless Steel Cabinet
- Voltage: 120 VAC, 4 amps, 60 Hz
- Alarm light output
- Emergency Stop
- NO PLANT AIR needed

## Controller

## Belt Drive in-feed hopper

- Large hopper capacity
- Holds 40 to 60 flat cases
- Flat length 14" to 40"
- Flat height 14" to 28"
- Weighted pusher
- Friction belt to feed cases



- Independent speed control
- Spring loaded for various case thickness
- 48" overall length
- Stainless steel and aluminium construction
- Robust design

## Hugger Belt Drive System

## Re-Stacker

- Restacks all cases
- Adjustable holding brushes
- Continuous operation - no need to stop process for material loading and unloading
- Optional reject for inspection systems



150 William Street Perth Amboy, NJ 08861

1-800-298-8936

Phone: 732-324-0800

Fax: 732-324-4488

Email: [sales@hsausa.com](mailto:sales@hsausa.com)

[www.hsausa.com](http://www.hsausa.com)