

Pigment White Ink

- Opaque white color
- Ideal for dark color non-porous substrates such as rubbers, cables, cosmetic boxes, and auto parts.



JR-002 Heatless Ink

Ink for inkjet printer:

Cartridge Type	Thermal Inkjet 45Si Cartridge
Color	White
Ink Type	Solvent based ink
De-cap Time	
Printing Parameters	Voltage: 9.0 V Pulse Width:1.8us
Pulse Warm	OFF, Recommended
Shelf Life	6 months
Heater Requirements	No dryer necessary
Maximum Frequency	12kHz
Storage	Store in a well-ventilated place. Keep container tightly closed. Keep cool. Store locked up.

Ink Handling and Maintenance

Please clean (wipe) the print head before use.

- Put on appropriate personal protective equipment
- Prohibition of dropping and throwing.
- Avoid contact with skin, eyes and clothing.
- Do not breathe vapors. Use only in a well-ventilated area.
- Use a ventilation, local exhaust if vapor or aerosol will be generated.
- Keep away from fire, sparks and heated surfaces.
- Take precautionary measures against electrostatic discharges.
- When using do not eat or drink. Wash hands thoroughly after handling.
- Do not store ink in high or freezing temperature.
- Keep away from heat and direct sunlight.
- Do not store ink with acids, oxidizing agents or explosives.
- Keep containers tightly closed in a dry, cool and well-ventilated place.
- Do not release into soil, sewers, river, or the public water courses.
- At the time of the leakage of contents: Absorb or cover with dry earth, sand or other non-combustible material and transfer to sealable containers. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.



150 William Street
Perth Amboy, NJ 08861
Toll Free: 1-800-298-8936
Phone: 732-324-0800
Fax: 732-324-4488
E-mail: sales@hsausa.com
Web Site: www.hsausa.com