Red Ink

- Red color
- Prints on: blister foils, aluminium, OPP, pet film, nylon, UV laminated papers, and regular semi and non porous substrates.



2.0mm : ABCDEFGHI12345678 2.5mm : ABCDEF123456 3.0mm : ABCD12345

JR-004 Heatless Ink

Dye Red

Cartridge Type	Thermal Inkjet 45Si Cartridge
Color	Red
Ink Type	Solvent based ink
De-cap Time	1 hour under normal conditions & environment
Printing Parameters	Voltage: 9.0 V Pulse Width:1.8ms
Pulse Warm	OFF, Recommended
Shelf Life	6 months from fill date
Heater Require- ments	No dryer necessary
Maximum Frequen- cy	12kHz
Storage	15 DegreeC~35 DegreeC (59F ~ 95F)

Ink Handling and Maintenance

- Please clean (wipe) the print head before use.
- Wipe with dry lint-free cloth; Do not clean with water

Benefits

- This fast drying ink doesn't require a heater and is perfect for the blister pharmaceutical packaging industry
- Heat resistant ink won't fade or change colour in blister process



150 William Street Perth Amboy, NJ 08861 Toll Free: 1-800-298-8936 Phone: 732-324-0800 Fax: 732-324-4488 E-mail: sales@hsausa.com

E-mail: sales@hsausa.com
Web Site: www.hsausa.com